

# 24-0020

Class 0 14" / 36cm Red



|                |  |                                |
|----------------|--|--------------------------------|
| Class          | 0  |                                |
| Max Use        | 1000V  |                                |
| Category       | A/Z/C  |                                |
| ARC            | APC2*  | ATPV - 8.5 cal/cm <sup>2</sup> |
| Cuff           | Straight with beaded edge                              |                                |
| ASTM D120 Type | 2  |                                |
| Colour         | Red  |                                |
| Length         | 14" / 36cm   |                                |
| Sizes          | 8-11   |                                |
| Packaging      | 1 pair p/polybag and individual box. 10 pairs p/carton |                                |

### Features & Benefits

- Made from 100% natural high grade rubber latex
- Smooth chlorinated surface finish and rolled cuff edge aid donning and doffing
- Environmentally friendly dipping process free from the use of solvents
- Ergonomic design and finger shape minimises hand fatigue
- Increased flexibility in cold environments
- Silicone-free
- Double certification EN 60903 and ASTM D120



### Applications / Industries

- Power Utilities and Public Works
- Electric Public Transport Maintenance
- EV Battery Manufacturing and assembly
- EV Aftermarket Service and Maintenance
- Electrical Maintenance
- Excavation and Cable Laying
- Cable Jointing
- Field Services



### Performance



Manufactured and tested in accordance with IEC 60903, EN 60903 and ASTM D120.



### Special Categories Classes

Meets the special properties:

A-Acid C-Extreme low temperature  
H-Oil resistant Z-Ozone  
R = A + Z + H

### Product Packaging

Each pair is supplied in an air sealed polybag and individual box.

Outer cartons contain 10 pairs of individual pair boxes.



| CLASS          | LENGTH CM/INCH |       | CATEGORIES | PROOF TEST VOLTAGE AC/DC | MAXIMUM USE VOLTAGE AC/DC | SIZES        | ARC                                 |
|----------------|----------------|-------|------------|--------------------------|---------------------------|--------------|-------------------------------------|
| Class 00 Beige | 28/11          | 36/14 | A/Z/C      | 2.500/10.000             | 500/750                   | 8, 9, 10, 11 | APC1*<br>- 8.4 cal/cm <sup>2</sup>  |
| Class 0 Red    | 28/11          | 36/14 | A/Z/C      | 5.000/20.000             | 1.000/1.500               | 8, 9, 10, 11 | APC2*<br>- 8.5 cal/cm <sup>2</sup>  |
| Class 1 White  | 36/14          |       | R/C        | 10.000/40.000            | 7.500/11.250              | 8, 9, 10, 11 | APC2*<br>- 10.6 cal/cm <sup>2</sup> |
| Class 2 Yellow | 36/14          |       | R/C        | 20.000/50.000            | 17.000/25.500             | 8, 9, 10, 11 | ATPV - 21.0 cal/cm <sup>2</sup>     |
| Class 3 Green  | 36/14          |       | R/C        | 30.000/60.000            | 26.500/39.750             | 8, 9, 10, 11 | ATPV - 40.5 cal/cm <sup>2</sup>     |
| Class 4 Orange | 41/16          |       | R/C        | 40.000/70.000            | 36.000/54.000             | 9, 10, 11    | ATPV - 36.2 cal/cm <sup>2</sup>     |

\* When tested according to GS-ET-42-1:2019-2