

63 7620

Medium weight cut F
impact glove with
sandy nitrile palm coating



Gauge	13gg
Colour	Grey liner / Black coating
Cuff Style	Knit wrist
Length	220-270mm
Sizes	6/XS - 13/4XL
Packaging	Vend packed per pair FSC wrap / 6 pairs in an FSC paper bundle Sizes 6, 7, 11, 12 & 13 - 36 Pairs / Carton Sizes 8, 9 & 10 - 72 Pairs / Carton

Features & Benefits

- Medium weight 13 gauge glove
- EN388: 2016+A1:2018 level F cut resistance
- EN388:2016+A1 2018 P impact protection
- EN407: 2020 contact heat level 1
- Slim 5.5mm TPR bumpers for high dexterity and wearer comfort
- Sandy nitrile palm coating provides good dry and wet grip
- Thumb crotch reinforced in high wear zone
- Tested after washing to domestic and industrial wash standards



Applications / Industries

- Oil and gas
- Energy Extraction
- Mining
- Metal fabrication / Stamping
- Machinery and equipment
- Construction and scaffolding
- Utilities



Performance

EN388: 2016



4 X 4 2 F P

EN407: 2020



X 1 X X X X



ANSI / ISEA 138



Sizing Cuff Colours

Size	6 X-Small	7 Small	8 Medium	9 Large	10 X-Large	11 2X-Large	12 3X-Large	13 4X-Large
Colour coded cuff	Yellow	Blue	Green	Red	Black	Brown	White	Grey